Varsian number 1

Printing date 20.04.2023 Version number 1.0 Revision: 20.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Defense-Man

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture Turf fertilizer

Uses advised against

To be used only where there is a recognized need. Do not exceed the appropriate dose rates.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

TURF Handels GmbH Am Hartboden 48 A-8101 Gratkorn T: +43 3124 29064

F: +43 3124 29062

Further information obtainable from: Email: office@turf.at

1.4 Emergency telephone number:

+43 3124 29064

Available during office hours: Mo - Th: 8 a.m. - 4.30 p.m.

Fr: 8 a.m. - 2.30 p.m.

Call the national emergency number!

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Eye Dam. 1 H318 Causes serious eye damage.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

Additional information: For the wording of the hazard categories, see section 16.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms







GHS05

HS05 GH

Signal word Danger

Version number 1

Printing date 20.04.2023 Version number 1.0 Revision: 20.04.2023

Trade name: Defense-Man

(Contd. of page 1)

Hazard-determining components of labelling:

manganese sulphate

Hazard statements

H318 Causes serious eye damage.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe dust.

P280 Wear eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: The mixture does not contain PBT substances $\geq 0,1$ %. **vPvB:** The mixture does not contain vPvB substances $\geq 0,1$ %.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

[% (w/w)]

CAS: 7785-87-7 EINECS: 232-089-9 Index number: 025-003-00-4 Reg.nr.: 01-2119456624-35-XXXX	manganese sulphate STOT RE 2, H373 Eye Dam. 1, H318 Aquatic Chronic 2, H411	25 – 80%
CAS: 77-92-9 EINECS: 201-069-1 Index number: 607-750-00-3 RTECS: GE 7350000 Reg.nr.: 01-2119457026-42-XXXX	Citric acid • Eye Irrit. 2, H319; STOT SE 3, H335	5 – < 20%
CAS: 6915-15-7 EINECS: 230-022-8	I-Malic acid Eye Irrit. 2, H319	5 – 20%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

In case of discomfort or doubt, seek medical advice.

(Contd. on page 3)

Version number 1

Printing date 20.04.2023 Version number 1.0 Revision: 20.04.2023

Trade name: Defense-Man

(Contd. of page 2)

If unconscious, use a stable lateral position and do not administer anything through mouth.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off contaminated clothing and wash it before reuse.

Seek medical treatment.

After eye contact:

Rinse opened eye for several minutes under running water.

Remove contact lenses, if present and easy to do. Continue rinsing.

Consult an ophthalmologist or eye clinic immediately.

After swallowing:

Rinse mouth.

Do NOT induce vomiting.

If the patient is conscious, make him drink water.

Call a doctor immediately.

Never administer anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Causes severe eye irritation or damage.

May cause skin irritation on prolonged or repeated use.

Swallowing may cause nausea and diarrhea.

Prolonged overexposure to manganese Sulfates may cause headache, apathy, muscle weakness and neurological effects such as euphoria, impulsiveness and insomnia.

4.3 Indication of any immediate medical attention and special treatment needed

Depending on the condition of the patients, the doctor must assess the symptoms and the overall general condition.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

COx

Metal Oxides/Oxides

5.3 Advice for firefighters

Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

(Contd. on page 4)

Version number 1

Printing date 20.04.2023 Version number 1.0 Revision: 20.04.2023

Trade name: Defense-Man

(Contd. of page 3)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Restricted access to the affected area until cleaning work is completed.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Avoid contact with skin and eyes.

Avoid formation of dust.

Do not breathe dust.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Pick up dry.

Avoid formation of dust.

Clean with water.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation.

Keep receptacles tightly sealed.

Avoid contact with skin and eyes.

Avoid breathing dust.

Eye wash bottles and emergency showers should be provided in the immediate area near the workplace.

Use personal protective equipment as required.

Observe protective measures and safety instructions.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store in dry conditions.

Store receptacle in a well ventilated area.

Store in accordance with local/regional/national/international regulations.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from feeding stuff.

Store away from oxidising agents.

Further information about storage conditions:

Keep container tightly sealed.

(Contd. on page 5)

Version number 1

Printing date 20.04.2023 Version number 1.0 Revision: 20.04.2023

Trade name: Defense-Man

(Contd. of page 4)

Protect container from damage.

Protect from frost.

Recommended storage temperature: room temperature

Storage class: 11

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

on a contract position	
Ingredients with lin	nit values that require monitoring at the workplace:
CAS: 7785-87-7 ma	nganese sulphate
IOELV (EU)	Long-term value: 0.2* 0.05** mg/m³ as Mn; *inhalable, **respirable fraction
MAK (Austria)	Short-term value: 1.6 E, 0.16 A mg/m³ Long-term value: 0.2 E, 0.05 A mg/m³ Als Mn berechnet
AGW (Germany)	Long-term value: 0.02A; 0.2E mg/m³ 8(II);DFG,Y,10, 20
LEP (Spain)	Long-term value: 0.2 *0.05 mg/m³ VLI, como Mn; *respirable, d,
VLEP (France)	Long-term value: 0.05* 0.20** mg/m³ *fraction alvéolaire **inhalable; en manganèse
WEL (Great Britain)	Long-term value: 0.2* 0.05** mg/m³ as Mn *inhalable fraction **respirable fraction
VL (Italy)	Long-term value: 0.2 mg/m³ Frazione inalabile; come Mn
WGW (Netherland)	Long-term value: 0.2* 0.05** mg/m³ als Mn; *inhaleerbaar **respirabel
CAS: 77-92-9 Citric acid	
AGW (Germany)	Long-term value: 2 E mg/m³ 2(I);DFG, Y

Regulatory information

IOELV (EU): (EU) 2019/1831

MAK (Austria): GKV 2020, 156. Verordnung, 09.04.2021, Teil II

AGW (Germany): TRGS 900

LEP (Spain): Límites de exposición profesional para agentes químicos

VLEP (France): ED 1487 05.2021 WEL (Great Britain): EH40/2020 VL (Italy): D.lgs. n. 81/2008

WGW (Netherland): Grenswaarden gezondheidsschadelijke stoffen

DNELs

CAS: 7785-87-7 manganese sulphate

Dermal Long-term exposure - systemic effects 0.002 mg/kg bw/d (consumer)

(Contd. on page 6)

Version number 1

Printing date 20.04.2023 Version number 1.0 Revision: 20.04.2023

Trade name: Defense-Man

(Contd. of page 5)

		(Conta. or page 3)
		0.004 mg/kg bw/d (workers)
Inhalative	Long-term exposure - systemic effects	0.043 mg/m³ (consumer)
		0.2 mg/m³ (workers)
	Long-term exposure - local effects	0.2 mg/m³ (workers)

PNECs

CAS: 7785-87-7 manganese sulphate

fresh water 0.03 mg/l sea water 0 mg/l intermittent release (fresh water) 0.088 mg/l STP 56 mg/l

sediment (fresh water) 0.011 mg/kg dw sediment (sea water) 0.001 mg/kg dw soil 25.1 mg/kg dw

Ingredients with biological limit values:

CAS: 7785-87-7 manganese sulphate

BGW (Germany) 20 µg/l

Untersuchungsmaterial: Vollblut

Probennahmezeitpunkt: bei Langzeitexposition: am Schichtende nach mehreren

vorangegangenen Schichten, Expositionsende bzw. Schichtende

Parameter: Mangan

Regulatory information BGW (Germany): TRGS 903

Additional Occupational Exposure Limit Values for possible hazards during processing:

The national dust limits must be observed in the event of dust generation.

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Appropriate engineering controls

No further data; see section 7.

Technical measures and the use of suitable working methods take priority over the use of personal protective equipment.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Do not eat or drink while working.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Immediately remove all soiled and contaminated clothing.

Prevent formation of dust.

Do not breathe dust.

Protective clothing needs to be selected specifically for the workplace, depending on concentrations and quantities of the hazardous substances handled. The chemical resistance of the protective equipment should be enquired at the respective supplier.

(Contd. on page 7)



Printing date 20.04.2023 Version number 1.0 Revision: 20.04.2023

Trade name: Defense-Man

(Contd. of page 6)

Eye wash bottles and emergency showers should be provided in the immediate area near the workplace.

Respiratory protection: Wear dust mask during formation of dust.

Hand protection



Protective gloves

EN 374

The glove material has to be impermeable and resistant to the product/ the substance/ the mixture.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Tightly sealed goggles

EN 166

Body protection: Protective work clothing

Environmental exposure controls

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Solid

Colour: White powder with dark powder

Odour: Odourless

Odour threshold: No information available.

Melting point/freezing point: No information available.

Boiling point or initial boiling point and boiling

range No information available.

Flammability Not determined.

Lower and upper explosion limit

Lower: No information available.

(Contd. on page 8)



Printing date 20.04.2023 Version number 1.0 Revision: 20.04.2023

Trade name: Defense-Man

(Contd. of page 7)

Upper: No information available.

Flash point: Not applicable.

Decomposition temperature:PH
No information available.
No information available.

Viscosity:

Kinematic viscosity Dynamic:Not applicable.
Not applicable.

Solubility

water: Soluble.

Partition coefficient n-octanol/water (log value)

77-92-9 Citric acid -1,6 log Kow

Vapour pressure: Not applicable.

Density and/or relative density

Density: No information available.

Vapour densityNot applicable.Particle characteristicsSee section 3.

9.2 Other information

Appearance:

Form: Powder

Important information on protection of health

and environment, and on safety.

Ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

Change in condition Softening point/range

Oxidising properties None.

Evaporation rate Not applicable.

Information with regard to physical hazard

classes

Explosives void Flammable gases void **Aerosols** void Oxidising gases void Gases under pressure void Flammable liquids void Flammable solids void Self-reactive substances and mixtures void **Pyrophoric liquids** void Pyrophoric solids void Self-heating substances and mixtures void Substances and mixtures, which emit flammable gases in contact with water void Oxidising liquids void Oxidising solids void

(Contd. on page 9)



Printing date 20.04.2023 Version number 1.0 Revision: 20.04.2023

Trade name: Defense-Man

(Contd. of page 8)

Organic peroxidesvoidCorrosive to metalsvoidDesensitised explosivesvoid

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No hazardous reactions known if stored and used as prescribed.
- 10.2 Chemical stability No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials:

oxidizing agent

Bases

10.6 Hazardous decomposition products:

No decomposition if used and stored according to specifications.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 v	LD/LC50 values relevant for classification:		
CAS: 7785	S: 7785-87-7 manganese sulphate		
Oral	LD50	2,150 mg/kg (rat)	
Inhalative	LC50/4h	> 4.45 mg/l (rat)	
CAS: 77-92-9 Citric acid			
Oral	LD50	5,400 mg/kg (mouse)	
Dermal	LD50	> 2,000 mg/kg (rat)	
CAS: 6915-15-7 I-Malic acid			
Oral	LD50	3,500 mg/kg (rat)	
Dermal	LD50	20,000 mg/kg (rat)	

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Causes serious eye damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 10)

Vorsion number 1

Printing date 20.04.2023 Version number 1.0 Revision: 20.04.2023

Trade name: Defense-Man

(Contd. of page 9)

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

CAS: 7785-87-7 manganese sulphate

LC50 (96 h) 49.9 mg/l (fish)

CAS: 77-92-9 Citric acid

LC50 (48 h) 440 mg/l (fish)

CAS: 6915-15-7 I-Malic acid

EC50 (48 h) 240 mg/l (daphnia)

12.2 Persistence and degradability

For the inorganic ingredients, the methods for determining biodegradability are not applicable.

77-92-9 Citric acid 97 % (28 d)

12.3 Bioaccumulative potential

77-92-9 Citric acid -1,6 log Kow

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: The mixture does not contain PBT substances ≥ 0.1 %.

vPvB: The mixture does not contain vPvB substances $\geq 0,1 \%$.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark: Toxic for fish

Additional ecological information:

General notes:

Toxic to aquatic life with long lasting effects.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Only dispose of product residues via authorised companies according to local legislation.

European waste catalogue

Notes: The European Waste Catalogue (EWC) classifies waste materials and categorises them according to what they are and how they were produced. This may cause other classifications. The final decision belongs to the last user.

(Contd. on page 11)



Printing date 20.04.2023 Version number 1.0 Revision: 20.04.2023

Trade name: Defense-Man

(Contd. of page 10)

02 01 08	agrochemical waste containing hazardous substances
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP14	Ecotoxic

UN3077

Uncleaned packaging:

Recommendation:

Dispose of packaging according to regulations on the disposal of packagings.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information


14.1 UN number or ID number ADR/RID/ADN, IMDG, IATA 14.2 UN proper shipping name

ADR/RID/ADN

IMDG, IATA

14.3 Transport hazard class(es)

ADR/RID/ADN, IATA



Class

Label

9 Miscellaneous dangerous substances and articles.

3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (manganese sulphate)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE,

SOLID, N.O.S. (manganese sulphate)

9

IMDG



Class 9 Miscellaneous dangerous substances and articles.

Label

14.4 Packing group

ADR/RID/ADN, IMDG, IATA

14.5 Environmental hazards:

Special marking (ADR/RID/ADN): Symbol (fish and tree)
Special marking (IATA): Symbol (fish and tree)

14.6 Special precautions for user Warning: Miscellaneous dangerous substances and

articles.

Hazard identification number (Kemler code): 90

(Contd. on page 12)



Printing date 20.04.2023 Version number 1.0 Revision: 20.04.2023

Trade name: Defense-Man

(Contd. of page 11)

EMS Number: F-A,S-F

Stowage Category A

Stowage Code SW23 When transported in BK3 bulk container, see

7.6.2.12 and 7.7.3.9.

14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

Transport/Additional information:

ADR/RID/ADN

Limited quantities (LQ) 5 kg
Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g

Transport category 3
Tunnel restriction code (-)

IMDG

Limited quantities (LQ) 5 kg
Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g

UN "Model Regulation": UN 3077 ENVIRONMENTALLY HAZARDOUS

SUBSTANCE, SOLID, N.O.S. (MANGANESE

SULPHATE), 9, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

(Contd. on page 13)

Varsion number 1

Printing date 20.04.2023 Version number 1.0 Revision: 20.04.2023

Trade name: Defense-Man

(Contd. of page 12)

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:

Information about limitation of use: Employment restrictions concerning juveniles must be observed. **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Training hints

Before handling, storage or use for the first time, employees must be informed about the properties of the substance and about measures taken to ensure safety and environmental protection.

Classification according to Regulation (EC) No 1272/2008

Serious eye damage/irritation Specific target organ toxicity (repeated exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS:

UmEnA GmbH http://umena.at

Email: office@umena.at

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

(Contd. on page 14)

Page 14/14

Safety data sheet according to 1907/2006/EC

TURF EXPERTS FOR YOU

Printing date 20.04.2023

Version number 1.0 Revision: 20.04.2023

Trade name: Defense-Man

(Contd. of page 13)

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

EU —